

Expert Net Control 2302-1



Remote I/O System with 4 switchable relay outputs and 8 passive signal inputs for DIN-rail mounting

Features

- 4 switchable, potential-free relay outputs, switching voltage 230 V AC 16 A / 24 V DC, 10 A
- All relay outputs individually switchable directly on the device, via HTTPS or command line tool
- Status and Power-up delay (0...9999 seconds) adjustable individually for each output after power blackout
- Simultaneous power-up of multiple outputs prevented by latency time of 1 second
- Switching of relay outputs dependent on sensor threshold or inputs possible
- Programmable turn-on/turn-off sequence
- 4-channel watchdog to monitor connected consumers (ICMP/TCP)
- Bicoloured LEDs on front panel display status information of inputs/outputs
- 8 passive signal inputs for monitoring NO and NC devices, e.g. door contacts, smoke detectors etc.
- Interface for optional sensor for environmental monitoring (temperature, humidity and air pressure)
- Messages by e-mail, Syslog and SNMP traps depending on threshold values of sensor metering and signal input as well
- Power supply also via external **DIN rail unit 7902** possible (not included in delivery)
- Comfortable configuration by web browser, Windows or Linux tool
- Firmware update via Ethernet during operation
- IPv6-ready
- HTTP/HTTPS, e-mail (SSL, STARTTLS), DHCP, Syslog

- SNMPv1, v2c, v3 (Get/Traps)
- TLS 1.0, 1.1, 1.2
- Radius and Modbus TCP support
- Configuration and control via Telnet
- IP Access Control List
- Android and iOS app *Gude Control* allows access from anywhere
 - Low internal power consumption, typ. 2 W
 - Developed and manufactured in Germany



Electrical Connections

- Terminal clamps for power supply with 230 V AC or 24 V DC
- 4 switchable outputs (terminal clamp)
- 8 passive signal inputs (terminal clamp)
- Ethernet connector RJ45 (10/100 Mbit/s)
- Sensor connector RJ45 for optional sensors or serial interface (RS232)

Technical Details

- LxHxD: 10.5 x 7 x 9 cm
- Weight: ca. 300 g
- Operating temperature: 0-50 °C
- Storage temperature: -20 - 70 °C
- Relative humidity: 0 - 95 % (non-condensing environment)

<input checked="" type="checkbox"/> IPv6	<input checked="" type="checkbox"/> SNMPv3
<input checked="" type="checkbox"/> HTTPS	<input checked="" type="checkbox"/> Telnet
<input checked="" type="checkbox"/> SSL	<input checked="" type="checkbox"/> Modbus TCP

Order code	Product	Feature	Power supply
2302-1	Expert Net Control 2302-1	4 switchable outputs, 8 passive signal inputs, 1 sensor port	230 V AC or 24 V DC
7101	Temperature Sensor 7101	Cable sensor with splash-proof sensor head (IP64), RJ45 connector, -20°C to +80°C, cable ca. 2.3 m	
7104 *	Temperature Sensor 7104	Cable sensor, RJ45 connector, -20°C to +80°C, cable ca. 2.3 m	
7105 *	Temp., Humidity Sensor 7105	Cable sensor, RJ45 connector, -20°C to +80°C, 0-90% humidity, cable ca. 2.3 m	
7106 *	Temp., Humidity, Air pressure Sensor 7106	Cable sensor, RJ45 connector, 20°C to +80°C, 0-90% humidity, 300-1100 hPa, cable ca. 2.3 m	
* Sensors also available with calibrated temperature range: 7104-2, 7105-2, 7106-2			
7201	Temperature Sensor 7201	Box case with RJ45 socket, -20°C to +80°C	
7202	Temp./Humidity Sensor 7202	Box case with RJ45 socket, -20°C to +80°C, 0-90% humidity	
7311	Optical Smoke Detector 7311	Overhead installation (d=100 mm), screw terminal NO or NC	
7312	Thermal Smoke Detector 7312	Overhead installation (d=100 mm), screw terminal NO or NC	
7313	Leakage Point Sensor 7313	13 mm two-tined, detects flooding, 4-core wire (2.5 m)	
7902	DIN Rail Power Supply Unit 7902	Power supply unit for DIN rail, 230 V AC / 12 VDC 1250 mA (not included in delivery)	
7940	Comb. Signaling Device 7940	Optical/acoustic alarm device, 100 dB sound pressure, 3-core connection cable (0.4 m)	

