

Expert Transfer Switch 8801-3



10

2

Automatic transfer switch (ATS) for redundant power supply of network components



Features

- Automatic transfer to alternate power supply if blackout of primary power supply occurs (A or B)
- Switches also if phase is shifted, typical transfer time 7-10 ms
- If primary power supply returns (A or B), automatic shift-in possible
- Load outlets: 1x IEC C19 (16A), 10x IEC C13 (10A)
- Thermofuse (10 A) prevents damages through overvoltages for 4 IEC C13 outlets
- Metering of energy, current, power factor, phase angle, frequency, voltage and active/apparent/reactive power
- 2 energy meters, one meter continuously, the other resettable
- Metering of residual current type A (RCM)
- LED display featuring status of power supply including phase-shift
- Clearly visible LED display for total current, IP address, sensor data and error reports
- 2 interfaces for plug-n-play sensors for environmental monitoring (temperature, humidity and air pressure)
- Messages by e-mail, Syslog and SNMP traps depending on threshold values of energy and sensor metering
- Comfortable configuration by web browser, Windows or Linux tool
- Firmware update via Ethernet during operation
- IPv6-ready
- HTTP/HTTPS, SSH, e-mail (SSL, STARTTLS), DHCP, Syslog
- SNMPv1, v2c, v3 (Get/Traps)
- TLS 1.0, 1.1, 1.2, 1.3
- Radius, Modbus TCP and MQTT (3.1.1) support
- Configuration and control over Telnet

- Access control via IP Access Control List
- Low power consumption
- Developed and manufactured in Germany

Electrical Connections

- 2 power supplies IEC C20, max. 16 A
- 10 load outlets IEC C13, max. 10 A
- Load outlet IEC C19, max. 16 A
- Ethernet connector RJ45 (10/100 Mbit/s)
- Galvanic isolated signal output (Sub-D 9-pin)
- 2 sensor interfaces (RJ45) for plug-n-play sensors

Technical Details

- 19 inch, 1 rack unit
- Dimensions: LxHxD: 43.9 x 4.4 x 19.5 cm (without brackets)
- Weight: ca. 2.5 kg
- Operating temperature: 0 - 50 °C
- Storage temperature: -20 - 70 °C
- Relative humidity: 0 - 95 % (non-condensing environment)



Power connectors on rear side of Expert Transfer Switch 8801-3

Order Code	Product	Feature	Max. Current
8801-3	Expert Transfer Switch 8801-3	ATS, 10 outlets IEC C13, 1 outlet IEC C19, RCM, thermal fuse	16 A
7205	Temp., Humidity Sensor 7205	Plug-n-play sensor, RJ45 connector, -20°C to +80°C, 0-90% humidity	
7206	Temp., Humidity, Air pressure Sensor 7206	Plug-n-play sensor, RJ45 connector, -20°C to +80°C, 0-90% humidity, 300-1100 hPa	
7207	Temp., Humidity, Signal Input Sensor 7209	Plug-n-play sensor, RJ45 connector, 20°C to +80°C, 0-90% humidity, 2 passive signal inputs	
0804	IEC Extension Cable 0804	Extension cable for IEC C13 to C14, length: 3 m	
0807	Cable Holder 0807	Cable holder with 13 fixation bridges for cable attachment on rear side of device	